

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036097 A1(51) International Patent Classification⁷: F16K 15/02
// 15/18, 17/04[DK/DK]; Wilhelmsro 230, DK-3480 Fredensborg (DK).
LEHD, John, F. [DE/DE]; Taunusblick 19, D-61479
Glashütten (DE).(21) International Application Number:
PCT/DK2003/000713(74) Agent: PLOUGMANN & VINGTOFT A/S; Sundkrogs-
gade 9, P.O. Box 831, DK-2100 Copenhagen (DK).

(22) International Filing Date: 21 October 2003 (21.10.2003)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
PA 2002 01597 21 October 2002 (21.10.2002) DK
60/419,592 21 October 2002 (21.10.2002) US(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility
model), DE, DK (utility model), DK, DM, DZ, EC, EE, EG,
ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP,
KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model),
SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(71) Applicant (*for all designated States except US*):
CUBEAIR A/S [DK/DK]; Solvang 24, DK-3450 Allerød
(DK).(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): BONNE, Adam

[Continued on next page]

(54) Title: A SAFETY VALVE

(57) Abstract: An apparatus for controlling flow in a
flowline under pressure, said apparatus comprising a
flow passage having a first end and a second end, and
hindering means for reducing the flow in the flow pas-
sage, the hindering means being arranged to move be-
tween a first and a second position under influence of
a pressure difference between the first end and the sec-
ond end of the flow passage. The reduction of the flow
in the flow passage is larger when the hindering means
is in the first and second position than when the hinder-
ing means is in an intermediate position between said
first and second positions. Hereby an improved safety
valve, which is adapted to shut off flow in a flow line
in two directions, is provided.